

# Material Safety Data Sheet

## Section 1: PRODUCT AND COMPANY INFORMATION

**Product Name(s):** Agilia®

**Product Identifiers:** Agilia®, Agilia® Architectural, Agilia® Vertical, Agilia® Horizontal, Agilia® Industrial, Agilia® BlockFill

**Manufacturer:**  
Lafarge North America Inc.  
12018 Sunrise Valley Drive, Suite 500  
Reston, VA 20191

**Information Telephone Number:**  
703-480-3600 (9am to 5pm EST)

**Emergency Telephone Number:**  
1-800-451-8346 (3E Hotline)

**Product Use:** Agilia® is used as a structural component in building and in construction.

**Note:** This MSDS covers many types of Agilia®. Individual composition of hazardous constituents will vary between types of Agilia®.

## Section 2: COMPOSITION/INFORMATION ON INGREDIENTS

Component	Percent (By Weight)	CAS Number	OSHA PEL -TWA (mg/m <sup>3</sup> )	ACGIH TLV-TWA (mg/m <sup>3</sup> )	LD <sub>50</sub> (mouse)	LC <sub>50</sub>
Crystalline Silica	0-90	14808-60-7	[(10) / (%SiO <sub>2</sub> +2)] (R); [(30) / (%SiO <sub>2</sub> +2)] (T)	0.025 (R)	NA	NA
Calcium Carbonate*	25-65	1317-65-3	15 (T); 5 (R)	10 (T); 3 (R)	NA	NA
Portland Cement*	10-30	65997-15-1	15 (T); 5 (R)	1 (R)	NA	NA
Calcium Hydroxide	15-25	1305-62-0	15 (T); 5 (R)	5 (T)	7300 mg/kg (oral)	NA
Calcium Oxide	0-5	1305-78-8	5 (T)	2 (T)	3059 mg/kg (intraperitoneal)	NA
Magnesium Oxide	0-4	1309-48-4	15 (T)	10 (T)	NA	NA
Calcium Sulfate*	0-2	13397-24-5	15 (T); 5 (R)	10 (T)	NA	NA
Particulate Not Otherwise Regulated	-	NA	15 (T); 5 (R)	10 (T); 3 (R)	NA	NA

Note: Exposure limits for components noted with an \* contain no asbestos and <1% crystalline silica

Agilia® is a mixture of gravel or rock, sand, Portland cement and water. It may also contain fly ash, slag, silica fume, calcined clay, fibers (metallic or organic) and color pigment. Chemical admixtures may also be present, in quantities comprising less than 3% of the material (refer to admixture MSDS).

## Section 3: HAZARD IDENTIFICATION

<b>WARNING</b>	
	<p>Corrosive - Causes severe burns. Toxic - Harmful by inhalation. (Contains crystalline silica)</p> <p>Use proper engineering controls, work practices, and personal protective equipment to prevent exposure to wet or dry product.</p> <p>Read MSDS for details.</p>
	<p>Respiratory Protection      Eye Protection</p> <p>Waterproof Gloves      Waterproof Boots</p>

### Section 3: HAZARD IDENTIFICATION (continued)

---

**Emergency Overview:** Unhardened Agilia® is an odorless semi-fluid, flowable, granular paste of varying color and texture. It is not combustible or explosive. Exposure of sufficient duration to wet Agilia® can cause serious, potentially irreversible tissue (skin, eye, respiratory tract) damage due to chemical (caustic) burns, including third degree burns.

Agilia® contains cement which is manufactured from materials mined from the earth and is processed using energy provided by fuels. Trace amounts of chemicals may be detected during chemical analysis such as: potassium and sodium sulfate compounds, chromium compounds, nickel compounds, and other trace compounds.

#### Potential Health Effects:

**Eye Contact:** Agilia® may cause immediate or delayed irritation or inflammation. Eye contact with wet Agilia® can cause moderate eye irritation, chemical burns and blindness. Eye exposures require immediate first aid and medical attention to prevent significant damage to the eye.

**Skin Contact:** Agilia® may cause dry skin, discomfort, irritation, severe burns, and dermatitis.

Burns: Exposure of sufficient duration to wet Agilia® can cause serious, potentially irreversible damage to skin, eye, respiratory and digestive tracts due to chemical (caustic) burns, including third degree burns. A skin exposure may be hazardous even if there is no pain or discomfort.

Dermatitis: Unhardened Agilia® is capable of causing dermatitis by irritation and allergy. Skin affected by dermatitis may include symptoms such as, redness, itching, rash, scaling, and cracking.

Irritant dermatitis is caused by the physical properties of Agilia® including alkalinity and abrasion.

Allergic contact dermatitis is caused by sensitization to hexavalent chromium (chromate) present in Agilia®. The reaction can range from a mild rash to severe skin ulcers. Persons already sensitized may react to the first contact with Agilia®. Others may develop allergic dermatitis after years of repeated contact with Agilia®.

**Inhalation (acute):** Breathing dust may cause nose, throat or lung irritation, including choking, depending on the degree of exposure. Inhalation of high levels of dust can cause chemical burns to the nose, throat and lungs.

**Inhalation (chronic):** Risk of injury depends on duration and level of exposure.

Silicosis: This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a seriously disabling and fatal lung disease. See Note to Physicians in Section 4 for further information.

Carcinogenicity: Agilia® is not listed as a carcinogen by IARC or NTP; however, Agilia® contains trace amounts of crystalline silica and hexavalent chromium which are classified by IARC and NTP as known human carcinogens.

Autoimmune Disease: Some studies show that exposure to respirable crystalline silica (without silicosis) or that the disease silicosis may be associated with the increased incidence of several autoimmune disorders such as scleroderma (thickening of the skin), systemic lupus erythematosus, rheumatoid arthritis and diseases affecting the kidneys.

Tuberculosis: Silicosis increases the risk of tuberculosis.

---

**Section 3: HAZARD IDENTIFICATION (continued)**


---

<b>Renal Disease:</b>	Some studies show an increased incidence of chronic kidney disease and end-stage renal disease in workers exposed to respirable crystalline silica.
<b>Ingestion:</b>	Do not ingest Agilia®. Although ingestion of small quantities of Agilia® is not known to be harmful, large quantities can cause chemical burns in the mouth, throat, stomach, and digestive tract.
<b>Medical Conditions Aggravated by Exposure:</b>	Individuals with lung disease (e.g. bronchitis, emphysema, COPD, pulmonary disease) or sensitivity to hexavalent chromium can be aggravated by exposure.

---

**Section 4: FIRST AID MEASURES**


---

<b>Eye Contact:</b>	Rinse eyes thoroughly with water for at least 15 minutes, including under lids, to remove all particles. Seek medical attention for abrasions and burns.
<b>Skin Contact:</b>	Wash with cool water and a pH neutral soap or a mild skin detergent. Seek medical attention for rash, burns, irritation, dermatitis, and prolonged unprotected exposures to wet Agilia®.
<b>Inhalation:</b>	Move person to fresh air. Seek medical attention for discomfort or if coughing or other symptoms do not subside.
<b>Ingestion:</b>	Do not induce vomiting. If conscious, have person drink plenty of water. Seek medical attention or contact poison control center immediately.
<b>Note to Physician:</b>	The three types of silicosis include:

- Simple chronic silicosis – which results from long-term exposure (more than 20 years) to low amounts of respirable crystalline silica. Nodules of chronic inflammation and scarring provoked by the respirable crystalline silica form in the lungs and chest lymph nodes. This disease may feature breathlessness and may resemble chronic obstructive pulmonary disease (COPD).
- Accelerated silicosis – occurs after exposure to larger amounts of respirable crystalline silica over a shorter period of time (5-15 years). Inflammation, scarring, and symptoms progress faster in accelerated silicosis than in simple silicosis.
- Acute silicosis – results from short-term exposure to very large amounts of respirable crystalline silica. The lungs become very inflamed and may fill with fluid, causing severe shortness of breath and low blood oxygen levels.

Progressive massive fibrosis may occur in simple or accelerated silicosis, but is more common in the accelerated form. Progressive massive fibrosis results from severe scarring and leads to the destruction of normal lung structures.

---

**Section 5: FIREFIGHTING MEASURES**


---

<b>Flashpoint &amp; Method:</b>	Non-combustible	<b>Firefighting Equipment:</b>	Agilia® poses no fire-related hazard. A SCBA is recommended to limit exposures to combustion products when fighting any fire.
<b>General Hazard:</b>	Avoid breathing dust. Wet Agilia® is caustic.		
<b>Extinguishing Media:</b>	Use extinguishing media appropriate for surrounding fire.	<b>Combustion Products:</b>	None.

---

**Section 6: ACCIDENTAL RELEASE MEASURES**

---

- General:** Place spilled material into a container. Avoid contact with skin. Wear appropriate protective equipment as described in Section 8. Scrape wet Agilia® and place in container. Allow material to dry or solidify before disposal. Do not wash Agilia® down sewage and drainage systems or into bodies of water (e.g. streams).
- Waste Disposal Method:** Dispose of Agilia® according to Federal, State, Provincial and Local regulations.

---

**Section 7: HANDLING AND STORAGE**

---

- Usage:** Cutting, crushing or grinding hardened cement, Agilia® or other crystalline silica-bearing materials will release respirable crystalline silica. Use all appropriate measures of dust control or suppression, and Personal Protective Equipment (PPE) described in Section 8 below.
- Storage Temperature:** Unlimited. **Storage Pressure:** Unlimited.
- Clothing:** Promptly remove and launder clothing that is wet with Agilia®. Thoroughly wash skin after exposure to wet Agilia®.

---

**Section 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION**

---

- Engineering Controls:** Use local exhaust or general dilution ventilation or other suppression methods to maintain dust levels below exposure limits.

**Personal Protective Equipment (PPE):**

- Respiratory Protection:** Under ordinary conditions no respiratory protection is required. Wear a NIOSH approved respirator that is properly fitted and is in good condition when exposed to dust above exposure limits.
- Eye Protection:** Wear ANSI approved glasses or safety goggles when handling wet Agilia® to prevent contact with eyes. Wearing contact lenses, when using Agilia®, is not recommended.
- Skin Protection:** Wear gloves, boot covers and protective clothing impervious to water to prevent skin contact. Do not rely on barrier creams, in place of impervious gloves. Remove clothing and protective equipment that becomes saturated with wet cement and immediately wash exposed areas.

---

**Section 9: PHYSICAL AND CHEMICAL PROPERTIES**

---

- |                          |                                       |                             |                       |
|--------------------------|---------------------------------------|-----------------------------|-----------------------|
| <b>Physical State:</b>   | Semi-fluid, Flowable, granular paste. | <b>Evaporation Rate:</b>    | NA.                   |
| <b>Appearance:</b>       | Variety of color (usually gray)       | <b>pH (in water):</b>       | 12 – 13               |
| <b>Odor:</b>             | None.                                 | <b>Boiling Point:</b>       | NA                    |
| <b>Vapor Pressure:</b>   | NA.                                   | <b>Freezing Point:</b>      | NA.                   |
| <b>Vapor Density:</b>    | NA.                                   | <b>Viscosity:</b>           | Varies.               |
| <b>Specific Gravity:</b> | 1.9 – 2.4                             | <b>Solubility in Water:</b> | Slightly (0.1 - 1.0%) |



**Section 16: OTHER INFORMATION**
**Abbreviations:**

>	Greater than	NA	Not Applicable
ACGIH	American Conference of Governmental Industrial Hygienists	NFPA	National Fire Protection Association
CAS No	Chemical Abstract Service number	NIOSH	National Institute for Occupational Safety and Health
CERCLA	Comprehensive Environmental Response, Compensation and Liability Act	NTP	National Toxicology Program
		OSHA	Occupational Safety and Health Administration
CFR	Code for Federal Regulations	PEL	Permissible Exposure Limit
CL	Ceiling Limit	pH	Negative log of hydrogen ion
DOT	U.S. Department of Transportation	PPE	Personal Protective Equipment
EST	Eastern Standard Time	R	Respirable Particulate
HEPA	High-Efficiency Particulate Air	RCRA	Resource Conservation and Recovery Act
HMIS	Hazardous Materials Identification System	SARA	Superfund Amendments and Reauthorization Act
IARC	International Agency for Research on Cancer	T	Total Particulate
		TDG	Transportation of Dangerous Goods
LC <sub>50</sub>	Lethal Concentration	TLV	Threshold Limit Value
LD <sub>50</sub>	Lethal Dose	TWA	Time Weighted Average (8 hour)
mg/m <sup>3</sup>	Milligrams per cubic meter	WHMIS	Workplace Hazardous Materials Information System
MSHA	Mine Safety and Health Administration		

This MSDS (Sections 1-16) was revised on March 1, 2011.

An electronic version of this MSDS is available at: [www.lafarge-na.com](http://www.lafarge-na.com) under the Sustainability section.

Lafarge North America Inc. (LNA) believes the information contained herein is accurate; however, LNA makes no guarantees with respect to such accuracy and assumes no liability in connection with the use of the information contained herein which is not intended to be and should not be construed as legal advice or as insuring compliance with any federal, state or local laws or regulations. Any party using this product should review all such laws, rules, or regulations prior to use, including but not limited to US and Canada Federal, Provincial and State regulations.

NO WARRANTY IS MADE, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OTHERWISE.