

Standards Compliance Certificate Lafarge Gypsum Products

This is to certify that the following materials supplied by Lafarge North America Inc. are manufactured in accordance with the listed ASTM standards.



bringing materials to *life*™

PRODUCT	DESCRIPTION AND USE	SPECIFICATION STANDARDS
Gypsum Board		
<input type="checkbox"/> Regular Drywall	For interior walls and ceilings.	ASTM C 1396, Section 5 and C 36
<input type="checkbox"/> Firecheck® Type X	Meets Type X requirements for interior walls and ceilings. Also conforms to ASTM C 442 Type X for use as backer board.	ASTM C 1396, Section 5 and C 36, Type X
<input type="checkbox"/> Firecheck® Type C	Exceeds Type X requirements for interior walls, ceilings and area separations requiring extended fire endurance ratings. Also conforms to ASTM C 442 Type X for use as backer board.	ASTM C 1396 Section 5 and C 36, Type X, Premium
<input type="checkbox"/> Mold Defense®	Mold-, mildew- and moisture-resistant drywall for interior construction.	ASTM C 1396, Section 7, C 630 and D 3273 (for mold)
<input type="checkbox"/> Mold Defense® Type X	Fire-, mold-, mildew- and moisture-resistant drywall for interior construction.	ASTM C 1396, Section 7, C 630, Type X and D 3273 (for mold)
<input type="checkbox"/> Mold Defense® Shaftliner Type X	Fire-, mold-, mildew- and moisture-resistant drywall for fire-rated shaftwalls and area separation walls.	ASTM C 1396, Section 6, C 442, Type X and D 3273 (for mold)
<input type="checkbox"/> Shaftliner Type X	Fire-resistant drywall for fire-rated shaftwalls and area separation walls.	ASTM C 1396, Section 6 and C 442, Type X
<input type="checkbox"/> Rapid Deco® Level 5	Level 5 skim-coated drywall for interior construction.	ASTM C 1396, Section 5, C 36 and factory-finished per ASTM C 840 Level 5
<input type="checkbox"/> Rapid Deco® Level 5 Type X	Fire-resistant, Level 5 skim-coated drywall for interior construction.	ASTM C 1396, Section 5, C 36, Type X and factory-finished per ASTM C 840 Level 5
<input type="checkbox"/> Rapid Deco® Level 5 with Mold Defense®	Mold- and mildew-resistant, Level 5 skim-coated drywall for interior construction.	ASTM C 1396, Section 5, C 36, factory-finished per ASTM C 840 Level 5 and D 3273 (for mold)
<input type="checkbox"/> Rapid Deco® Level 5 Type X with Mold Defense®	Fire-, mold- and mildew-resistant, Level 5 skim-coated drywall for interior construction.	ASTM C 1396, Section 5, C 36, Type X, factory-finished per ASTM C 840 Level 5 and D 3273 (for mold)
<input type="checkbox"/> Sagcheck	Sag-resistant drywall for interior and textured ceilings.	ASTM C 1396, Section 12, C 1395 and C 36
<input type="checkbox"/> Plasterbase	Drywall with a special bonding paper for veneer plaster finishes. Used for interior construction.	ASTM C 1396, Section 10 and C 588
<input type="checkbox"/> Firecheck® Plasterbase Type X	Fire-resistant drywall with a special bonding paper for veneer plaster finishes. Used for interior construction.	ASTM C 1396, Section 10 and C 588, Type X

PRODUCT	DESCRIPTION AND USE	SPECIFICATION STANDARDS
Gypsum Board		
<input type="checkbox"/> Protecta® AR 100 Type X with Mold Defense®	Abuse-, fire- and mold-resistant drywall for interior, high-traffic areas.	ASTM C 1396, Section 5 and C 36, Type X, D 3273 (for mold) and C 1629 (for abuse resistance)
<input type="checkbox"/> Protecta® HIR 300 Type X with Mold Defense®	High impact-, fire- and mold-resistant drywall for interior, high-traffic areas.	ASTM C 1396, Section 5 and C 36, Type X, D 3273 (for mold) and C 1629 (for abuse resistance)
<input type="checkbox"/> Sheathing	Moisture-resistant gypsum sheathing with treated core for exterior construction.	ASTM C 1396, Section 9 and C 79, Treated Core
<input type="checkbox"/> Firecheck® Sheathing Type X	Fire and moisture-resistant gypsum sheathing with treated core for exterior construction.	ASTM C 1396 Section 9 and C 79, Type X, Treated Core
<input type="checkbox"/> Soffitboard	For exterior use on the soffit side of eaves and other applications with indirect exposure to the elements.	ASTM C 1396, Section 8 and C 931
<input type="checkbox"/> Firecheck® Soffitboard Type X	Fire-resistant board for exterior use on the soffit side of eaves and other applications with indirect exposure to the elements.	ASTM C 1396, Section 8 and C 931, Type X
<input type="checkbox"/> Watercheck®	Water-resistant drywall for interior walls. Not for continuous, high-moisture or wet areas.	ASTM C 1396, Section 7 and C 630
<input type="checkbox"/> Fire Watercheck® Type X	Fire- and water-resistant drywall for interior walls. Not for continuous, high-moisture or wet areas.	ASTM C 1396, Section 7 and C 630, Type X
<input type="checkbox"/> Weather Defense Platinum®	Moisture- and mold-resistant sheathing with treated core and fiberglass mat coating for exterior construction.	ASTM C 1177, Treated Core
<input type="checkbox"/> Weather Defense Platinum® Type X	Moisture-, mold- and fire-resistant sheathing with treated core and fiberglass mat coating for exterior construction.	ASTM C 1177, Type X, Treated Core
<input type="checkbox"/> Weather Defense Platinum® Shaftliner Type X	Moisture-, mold- and fire-resistant sheathing with treated core and fiberglass mat coating for fire-rated shaftwalls and area separation walls.	ASTM C 1658, Section 6, Type X

Finishing Products		
<input type="checkbox"/> Rapid Coat®	Light-weight, all-purpose joint compound.	ASTM C 475
<input type="checkbox"/> Rapid Coat® Mid Weight	Mid-weight, all-purpose joint compound.	ASTM C 475
<input type="checkbox"/> Rapid Coat® All Purpose	Heavy-weight, all-purpose joint compound.	ASTM C 475
<input type="checkbox"/> Rapid Coat® Low Dust	All-purpose compound that creates less airborne dust during sanding compared to regular joint compounds.	ASTM C 475
<input type="checkbox"/> Rapid Deco® Level 5 Joint Compound	All-purpose compound designed to give a Level 5 finish when used with Rapid Deco Level 5 skim-coated drywall.	ASTM C 475 Fulfills ASTM C 840, Level 5
<input type="checkbox"/> Rapid Joint®	Setting-type compound with time-controlled hardening properties. Available set times: 20, 45 and 90 minutes.	ASTM C 475

JOB NAME: _____

CONTRACTOR: _____

DATE: _____



Lafarge North America Inc.
Reston, Virginia 20191
USA • (800) 237-5505

Lafarge Canada Inc.
Montreal, Quebec H3B 1L7
Canada • (866) 649-7786

www.lafargenorthamerica.com